







AIRPRO-2[®] Flushing Compressor

Effective, Easy Cleaning for Heating Systems

The Kammak AIRPRO-2 flushing compressor is designed for safe and easy removal of corrosion, sludge and scale debris from heating systems.

- Flushing of heating systems, central heating systems, underfloor heating systems/heating circuits
- Flushing of drinking water pipes
- Impulse flushing

- 1 HP, 8 bar high performance
- Hydrodynamic wash, Impulse flushing
- Flow reverser
- Light weight and compact with ergonomic design



KAMMAK

High performance
descaling pumps and
power flushing compressors

Additional Features

- Pressure regulator
- Pressure regulator indicator
- Pressure indicator
- High flow rate for maximum cleaning
- Rapid removal of system debris
- Oil-free dry piston air compressor
- Pressure regulator
- Oil-free dry piston air compressor

Technical Specification

Material of Construction	Metal
Tank Capacity	9 litres air tank
Dimensions	Height: 76cm/Width:50cm/Depth:35cm
Weight	Empty: 23kg. Full:29kg
Power Requirements	220-230V, 50Hz single phase motor, Europlug
Motor	750 W / 1HP
Pressure	1-8 bar max pressure
Flow Rate	110 l/min
Hose	2x2,5m 16mm flow-return hoses 1x2,5m 16mm tap water inlet hose 1x2,5m 16mm dump outlet hose
Physical Limitations	Maximum temperature range 60°C
Degree of protection	Thermal protection
Connections/fittings	3/4"



KAMMAK Ltd Şti

Cataltepe Mh BESOB 6. Sok No:9/1 16450 Bursa, TURKEY

Tel: +90 546 223 28 98 www.kammakpumps.com