



PROMAX-SHAKE[®] Flushing Compressor







Effective, Easy Cleaning for Heating Systems

The Kammak Machine is designed for safe and easy removal of corrosion, sludge and scale debris from heating systems.

- Flushing of heating systems, central heating systems, underfloor heating systems/heating circuits
- Flushing of drinking water pipes
- Impulse flushing
- Air Flush + Water Flush

- 1 HP, 8 bar high performance
- Hydrodynamic wash, Impulse flushing

- Flow reverser
- Light weight and compact with ergonomic design



KAMMAK

High performance
descaling pumps and
power flushing compressors

Additional Features

- Pressure regulator
- Pressure regulator indicator
- Pressure indicator
- High flow rate for maximum cleaning
- Rapid removal of system debris
- Oil-free dry piston air compressor
- Pressure regulator
- Oil-free dry piston air compressor

Technical Specification

Material of Construction	Polyethylene tank
Tank Capacity	45 litres water tank, 9 litres air tank
Dimensions	Height: 76cm/Width:36cm/Depth:50cm
Weight	Machine:31 kg Compressor: 15 kg
Power Requirements	220-230V, 50Hz single phase motor, Europlug
Motor	750 W / 1HP
Pressure	8 bar max pressure
Flow Rate	Net: 60 l/min
Hose	2x 2,5m 16mm flow and return hoses 1x2,5m 16mm tap water inlet hose
Physical Limitations	Maximum temperature range 60°C
Degree of protection	Thermal protection, Ip54
Connections/fittings	3/4"

Included ; 9 liter oil-free air compressor.



KAMMAK Ltd Şti

Cataltepe Mh BESOB 6. Sok No:9/1 16450 Bursa, TURKEY

Tel: +90 546 223 28 98 www.kammakpumps.com